



RGB PLUS Line T33 Light Tubes RGB+T33


Length: 0.5, 1, 1.5, 2-meter

Ends: thru-connect, terminated

Style: frosted

Wire Color: black, white

Output	
LED Type	SMD 5050
LED Channels	R-G-B
LED Count	144 LEDs per meter
Greyscale	16-bit, 65,536 dimming levels*
Viewing Angle	360-degrees
Control	
Individually Addressable	No (3 LEDs as one section)
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 48 pixels
Max Distance before Power Injection	approx. 2 meters
Electrical & Safety	
Input Voltage	24 VDC
Current	0.67 Amps / meter per channel
Power	16 Watts / meter per channel
Wire	20 AWG, 3C, UV protected
Inline power injection	via Rainmin Power T+'s & RGB+5A-24V
Physical	
Diameter	33 mm
Pitch	4cm
Weight	approx. 0.5kg. per meter
Housing	polycarbonate
Connector Type	LLT twist-lock
Lead/End Wire length	6" (standard)
Operating Temperature	Neg -25 to +60 Cel.



China HQ

42# 168 Industrial Park,
Jingmei Village,
Dongguan City,
Guangdong, 523000

86-0769-81013103

www.rainmin.com

* 8-bit via DDP.

Specifications as of August 2024 and are subject to change.

